

هو منتج جديد تم ترقيته بعد عبوات البلاط البلاط البورنيالي الملون، Kelin Epoxy Tile Intile IntelS Adhesive، ولكنه أيضا يجعل البناء أسهل فإنه لا يحتفظ فقط بلمس الجص البلاط البلاط الملون من الماء الملون، وترقية أداء المنتج، ولكن أيضا يجعل مكان الديكور وأكثر ملاءمة. نسيج ناعم، يظهر إلى حد كبير أسلوبك الزخرفية الفاخرة المنخفضة. أصناف الألوان، وجعل مكان الديكور تدع منتجك أكثر مقاومة للماء، مقاومة للاهتراء، والدليل Epoxy Course الصديقة للبيئة للبيئة الخاص بك تألق. دورة على الرطوبة. الرمل الطبيعي المكلس عند ارتفاع درجة الحرارة يجعل اللون أكثر طبيعية جميلة ولا يتلاشى أبدا. أيضا، فهي مشرقة مثل الخزف بعد الشحذ دون اصفرار أو إلحاح. بالإضافة إلى ذلك، يبدو السطح المشترك مناسباً تماماً للبلاط السيراميك، تماماً مثل الطبيعة نفسها.

نتاج **الصين بلاط لاصق المزود** يمكن استخدامها بشكل أفضل في مفاصل بلاط السيراميك والحجر والزجاج أو بلاط الفسيفساء على الحائط أو الدقيق في الحمام والمطبخ وغرفة النوم وهلم جرا. أستراليا منتجات البحث والتطوير المشتركة لتحقيق أداء أفضل، ومن خلال التوجيه الصيني للعلوم التوجيهات مراقبة الجودة الاستراتيجية، لجعل نوعية المنتجات مستقرة. **الصين الايبوكسي ملء الجص الصانع** لتزويدك بمنتجات عالية الجودة.



أصناف من الألوان لاختيارك. توفير أيضا ألوان مخصصة

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



توفير حل فجوة الغرفة بأكملها



عملية بناء موجزة



01  
Clean the tiles and keep it dry



02  
Polish with tile wax except the glazed tile



03  
Open & Watch, both sides can extruded meanwhile



04  
Screw on the nozzle, put on the grout gun



05  
Inclined cut the top of the nozzle in 45°



06  
Squeeze out 60-80cm long grout in the forepart



07  
Evenly squeeze out the tile agent along the gap



08  
Press the grout with professional glue-press tools



09  
Don't touch in 4-5 hours and remove excess grout then.



10  
Keep the tiles dry in 24 hours

## أداة الضغط المشترك المهنية



Two Component Caulking Gun



02  
Cutter Knife



03  
Pointing trowel



04  
Brush



05  
Forming Stick



06  
Perching Knife



07  
Masking Tape



08  
Stainless Steel Ball



09  
Cleaning Awl

## ميزة الشركة



## نظرة عامة على المصنع



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

## شهادة

